

## Product data sheet

Datum der Erstellung: 02.11.2016

<b>Article-Nr.:</b>	<b>108043</b>
<b>Type of Product:</b>	Canister, 20 Liter, electrostatic conductive, with max. level indicator
<b>Capacity (maximum):</b>	23,5 Liter
<b>Dimensions (W x D x H):</b>	ca. 185 x 500 x 290 mm
<b>Weight:</b>	ca. 1240 g
<b>Material:</b>	PEHD Hostalen GM 9350C black/new
<b>Surface Resistivity:</b>	$< 10^6 \Omega$
<b>Closure:</b>	Screw Cap
<b>Thread Size:</b>	S 60/61
<b>Material:</b>	PE-HD, Glas
<b>Seal:</b>	Alkozell 300: Thickness 4 mm

### Test Reports / Approvals:

Due to the level indicator this canister cannot have an UN approval for transportation outside the company ground

### Safety Notes

- On transport or storage of dangerous goods the regulations of each country must be fulfilled
- In every single case a canister must be tested on suitability and tightness
- The approved period of use amounts to 5 years maximum as long as there is no shorter timeframe noted in carriage regulations of the individual group
- During use a canister must be marked with mandatory letterings and Hazard Symbols

### Legal Bases

- European Agreement Concerning the international Carriage of Dangerous Goods by Road (ADR)
- Regulations on the International Transport of Dangerous Goods by Rail (RID)
- International Maritime Dangerous Goods Code (IMDG Code)
- Recommendations on the Transport of Dangerous Goods of the United Nations
- Technical Instructions for the safe Transport of Dangerous Goods by Air (ICAO-TI) laid down in the IATA-Dangerous Goods Regulations too.