

Product data sheet

Date of generation: 22.11.2012

Articl-Nr.:	107 940
Type of Product:	Canister, 60 liter, electro conductive
Capacity (maximum):	63,8 liter
Dimensions (W x D x H):	ca. 332 x 396 x 630 mm
Weight:	ca. 3000 g
Material:	PEHD
Surface Resistivity:	10 ⁶ Ω
Closure:	Screw Cap
Thread Size:	S 70/71
Material:	Lupolen 4261 A
Seal:	Alveocell, Dicke: 6 mm

Test Reports / Approvals:		
Report Nr.	Date	Testing Center
9754/3H1	12.02.1997	BAM- Federal Institute of Materials Research and Testing
110 106	11.01.1991	Deutsche Bundesbahn
K 92 141	05.05.1992	Staatliche Materialprüfanstalt Darmstadt
44.082	17.12.2001	OFI Kunststoffinstitut

Marking:

UN 3H1 / Y 1.2 / 150 / ..*

* completed with the last two numbers of the year of production

Safety Notes
<ul style="list-style-type: none"> • On transport or storage of dangerous goods the regulations of each country must be fulfilled • The maximum overpressure must not exceed 100 kPa at all • The approved period of use amounts to 5 years maximum as long as there is no shorter timeframe noted in carriage regulations of the individual group • Every single canister has to be tested on suitability and tightness before use • During use a canister must be marked with mandatory letterings and hazard symbols.

Legal Bases
<ul style="list-style-type: none"> • European Agreement Concerning the international Carriage of Dangerous Goods by Road (ADR) • Regulations on the International Transport of Dangerous Goods by Rail (RID) • International Maritime Dangerous Goods Code (IMDG Code) • Recommendations on the Transport of Dangerous Goods of the United Nations • Technical Instructions for the safe Transport of Dangerous Goods by Air (ICAO-TI) laid down in the IATA-Dangerous Goods Regulations too