

Datasheet

Part No.:	107713
Description	Flat canister 20 liter, S70/71, PE-HD, UN-Y approval dimensions: (W x D x H): 376 x 283 x 292 mm
Measurements (WxDxH)	376 x 283 x 292 mm
Volume:	20 l
Weight:	1,280 kg
Colour	nature
Material:	HDPE
Sealing material:	PE foam
Chemical resistance:	good
Closure type:	screw cap
Thread size:	S 70 / 71
Overflow volume:	22,0 l

Compliance / approvals

Document No.:	Date	Inspection authority:
311.760	23.07.2009	ofi
401.706	23.11.2009	ofi
312.086	12.03.2010	ofi
403.349/1	01.09.2010	ofi

UN approval:

3H1 / X1.9 / 250 / ...

Other approvals / marks:

- tightening torque 20-25 Nm
- with separate air vent canal
- emptied guarantee

Safety instructions:

On transport or storage of dangerous goods the regulations of each country must be fulfilled.
The maximum overpressure must not exceed 100 kPa at all.
The approved period of use amounts to 5 years maximum as long as there is no shorter timeframe noted in carriage regulations of the individual group.
Every single canister has to be tested on suitability and tightness before use.
During use a canister must be marked with mandatory letterings and hazard symbols.

Legal bases:

European Agreement Concerning the international Carriage of Dangerous Goods by Road (ADR).
Regulations on the International Transport of Dangerous Goods by Rail (RID).
International Maritime Dangerous Goods Code (IMDG Code).
Recommendations on the Transport of Dangerous Goods of the United Nations.
Technical Instructions for the safe Transport of Dangerous Goods by Air (ICAO-TI) laid down in the IATA-Dangerous Goods Regulations too.

